



Motorcraft® Power Unit (eDrive) Assy Lubricants – Quick Reference Lubricant Applications and Capacities Chart

VEHICLE	AXLE LOCATION	FLUID REFILL QTS (LTRS)	MODEL YEAR										
			2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	
SUV													
Mustang Mach E (Base AWD) (MY21-) [1]	Front	0.92 (0.875)									LV	LV	ULV
Mustang Mach E (All)	Rear	4.07 (3.85)									ULV	ULV	ULV
Mustang Mach E (GT AWD)	Front	3.43 (3.25)									ULV	ULV	ULV
Corsair PHEV (RWD) [1]	Rear	1.03 (0.975)									LV	LV	
Corsair PHEV (RWD) (MY23-)	Rear	1.03 (0.975)											ULV
TRUCKS													
F150 Lightning	Front	4.0 (3.79)										ULV	ULV
F150 Lightning	Rear	4.76 (4.5)										ULV	ULV
eTransit	Rear	4.07 (3.85)										ULV	ULV

Note: None of the Electric Drive Assemblies will use friction modifiers.

[1] MY21 original use of XY-75W85-QL has changed over for top-off and drain/fill to MERCON® LV. XY-75W85-QL and MERCON® LV are compatible for this application.

ULV	MERCON® ULV Part number XT-12-QULV (Quarts)
LV	MERCON® LV Part number XT-10-QLVC (Quarts)