



Motorcraft® Power Unit (eDrive) Assy Lubricants – Quick Reference Lubricant Applications and Capacities Chart

VEHICLE	AXLE LOCATION	FLUID REFILL QTS (LTRS)	MODEL YEAR											
			2016	2017	2018	2019	2020	2021	2022	2023	2024	2025		
SUV														
Mustang Mach E (Base AWD) (MY21-) [1]	Front	0.92 (0.875)							LV	LV	ULV	ULV	ULV	
Mustang Mach E (All) (MY21-MY23)	Rear	4.07 (3.85)							ULV	ULV	ULV			
Mustang Mach E (All) (MY24-)	Rear	4.44 (4.2)										ULV	ULV	
Mustang Mach E (GT AWD)	Front	3.43 (3.25)							ULV	ULV	ULV	ULV	ULV	
Corsair PHEV (RWD) [1]	Rear	1.03 (0.975)							LV	LV				
Corsair PHEV (RWD) (MY23-)	Rear	1.03 (0.975)									ULV	ULV	ULV	
TRUCKS														
F150 Lightning	Front	4.0 (3.79)									ULV	ULV	ULV	ULV
F150 Lightning	Rear	4.76 (4.5)									ULV	ULV	ULV	ULV
E-Transit	Rear	4.07 (3.85)									ULV	ULV	ULV	ULV

Note: None of the Power Unit Assy's will use friction modifiers.

[1] MY21 original use of XY-75W85-QL has changed over for top-off and drain/fill to MERCON® LV. XY-75W85-QL and MERCON® LV are compatible for this application. WSMs provide the Front Electric Drive Assy Part number and use of MERCON® LV or MERCON® ULV

ULV	MERCON® ULV Part number XT-12-QULV (Quarts)
LV	MERCON® LV Part number XT-10-QLVC (Quarts)